


OPTRAL



Mini ZIPCORD / I-V(ZN)H 2x1

Duplex Patchcord Cable



Cable description

- 01. Tight Buffer Fibre (0.9 mm)
- 02. Strength Members
- 03. Outer Jacket

Fire performance

Flame retardant (IEC 60332-1)
Halogen free (IEC 60754-1/-2)
Low smoke emission (IEC 61034-2)

Applications

Indoor
Jumper and pigtail connections
Direct connection to terminal equipments
Based on DIN VDE 0888 part 6

Options

Easy-Strip Buffer
Special Colour Code

Advantages

Flexible / Resilient / Totally dielectric / Direct connectorization.



SPECIFICATIONS

	Mini-ZIPCORD-25	Mini-ZIPCORD-21	Mini-ZIPCORD-18	Mini-ZIPCORD-16
Fibres	2			
Identification	Colours			
Strength Members	Aramid Yarns			
Outer Jacket	LSZH ¹			
Colour	ORG (RAL2003) MM62 / BLU (RAL5015) MM50-OM2 / AQU (RAL6027) OM3 / VIO (RAL4003) OM4 / LIME GREEN OM5 / YLW (RAL1021) OS2 / IVORY (RAL1015) G657			
Weight (Kg/Km)	12.2	9	7.5	5.5
Outer Ø (mm)	2.5 x 5.3 ± 0.1	2.1 x 4.4 ± 0.1	1.8 x 3.8 ± 0.1	1.6 x 3.4 ± 0.1
Tensile Load Oper. / Inst (N)	300 / 500	240 / 400	80 / 130	80 / 130
Max. Crush (N/dm)	500	300	300	300
Temperature Range	-5°C to +60°C (Storage and Operation) / -5°C to +60°C (Installation) - (IEC 60794-1-22 F1)			
Min. Bending Radius (mm)	15 x Outer Ø (IEC 60794-1-21 E11)			
Max. Length (m)	2000			

Standards

Mechanical and Environmental tests according to IEC 60794-1-21 and IEC 60794-1-22.

Fibres colour code: Red – Green

¹ LSZH - Halogen free, low smoke and flame retardant thermoplastic compound.