


.....

OPTRAL



FLAT / I-V(ZN)HH 2x1 Duplex Patchcord Cable



Cable description

- 01. Tight Buffer Fibre (0.9 mm)
- 02. Strength Members
- 03. Inner Jacket
- 04. Outer Jacket

Fire resistance

Flame retardant (IEC 60332-1)
Halogen free (IEC 60754-1/-2)
Low smoke emission (IEC 61034-2)

Applications

Indoor
Direct connection to terminal equipments
Based on DIN VDE 0888 Part 6

Options

Easy-Strip Buffer
Special colour code

Advantages

Flexible / Resilient / Totally dielectric / Direct connectorization.



SPECIFICATIONS

Fibres	2
Strength members	Aramid Yarns
Inner jacket	LSZH ¹
Subcables Ø (mm)	2.9 ± 0.1
Outer jacket	LSZH ¹
Colour ²	ORG (RAL2003) MM62 / BLU (RAL5015) MM50-OM2 / AQU (RAL6027) OM3 / MAG (RAL4003) OM4 / LIME GREEN OM5 / YLW (RAL1021) OS-1/2
Weight (Kg/Km)	27
Outer Ø (mm)	4.0 x 6.7 ± 0.3
Max. Tensile Load (N)	400 (Operating) / 700 (Installation) - (IEC 60794-1-21 E1)
Max. Crush (N/dm)	750 (IEC 60794-1-21 E3)
Temperature Range	-5°C to +60°C (IEC 60794-1-22 F1)
Min. Bending Radius (mm)	15 x Outer Ø (IEC 60794-1-21 E11)
Max. Length (m)	2000

Standards

Mechanical and Environmental tests according to IEC 60794-1-21 and IEC 60794-1-22.

Inner jacket colour: Red – Green.

¹LSZH – Halogen free, low smoke and flame retardant thermoplastic compound.

² For singlemode fibre G.657 the jacket colour is ivory.

All technical specifications are subject to change without prior notice. Consult OPTRAL for the latest edition.

.....